

# **MATERIAL SAFETY DATA SHEET**

This Material Safety Data Sheet complies with the Canadian Controlled Products Act

		5	SECTION 1 -	PRODUC <sup>*</sup>	T IDE	NTIFICATION		
PRODUCT IDENTIFIER:	Waste Paint Hardener					Retail & Industrial (Commercial)		
PRODUCT USE:	Late	x Paint Ha	rdener					
SUPPLIER:	Napier Environmental Technologi Inc.				es In case of transporation emergency or product spill, contact:			
720 Eaton Way, Delta, British Columbia, Canada, V3M 6J9 Emergency telephone: (800) 663-9274, Telephone: (604) 526-0802, Facsimile: (605-7772)					In Canada- CANUTEC @ 613-996-6666 (24 hrs.)			
					In the Continental USA-			
		S	SECTION 2 –	HAZARDO	DUS II	   NGREDIENTS		
HAZARDOUS INGREDIENTS		% (W/W)	CAS NUMBER	LD50		LC50	EXPOSURE LIMITS	
Sodium Polyacrylate		60-100	Not assigned	gned > 5000 mg/kg (oral, rat) >2000 mg/kg (dermal, rabbit)		Not available	0.05 mg/m3 (respirable)	
			SECTIO	N 3 – PHY	'SICA	L DATA		
Physical state: solid					Vapour Density: not applicable			
Solubility: slightly soluble					Vapour Pressure: not applicable			
Odour and Appearance: white granular powder with no odor					Evaporation Rate: not applicable			
pH @ 20°C: not applicable						Boiling Point (°C): not applicable		
Density: 400 - 497 kilograms per cubic meter					Freezing Point (°C): not applicable			
Odour Threshol	Odour Threshold (ppm): not applicable					Coefficient of water/oil distribution: not determined		
		S	ECTION 4 – I	FIRE AND	EXPL	OSION DATA		
Flammability: No, product is non-flammable.					Flash Point (°C) and method: not applicable			
If yes, under what condition: Not applicable.					Upper Flammable limit (% volume): not applicable			
Means of Extinction: Dry chemical, alcohol foam, CO <sub>2</sub> , water					Lower Flammable limit (% volume): not applicable			
spray. Do not use direct water stream.					Autoignition temperature (°C): not applicable			
<b>Unusal Hazards:</b> Keep product dust away from ignition sources such as open flames, static discharge, etc. Under certain conditions, dust generation in air may cause a dust explosion if ignited.					Hazardous combustion products: may form toxic carbon monoxide and dioxides upon thermal decomposition.			
Explosion Data-								
Sensitivity to im	pact: N	lone						
Sensitivity to sta	atic dis	charge: N	one					
					1			

Issue: 10/29/04

# Waste Paint Hardener (Retail & Industrial)

#### **SECTION 5 – REACTIVITY DATA**

Chemical Stability: yes, stable under normal storage conditions

If no, under what conditions:

**Incompatibility with other substances:** yes **If so, under what conditions**: Strong alkalis

Reactivity, and under what conditions: none known

Hazardous Decomposition Products: Oxides of carbon may be liberated upon thermal decomposition

### **SECTION 6 – TOXICOLOGICAL PROPERTIES**

Primary route of entry: Eye contact and inhalation

Effects of Acute Exposure to Product: Product exposure may cause slight to moderate eye irritation. Inhalation of dust at low levels can cause lung inflammation and discomfort.

**Effects of Chronic Exposure to Product:** Prolonged exposure may cause eye dryness and lung tumors (based on lifetime studies on laboratory rats exposed to highly respirable product dust at less than 10 micron. At 0.8 mg/m3, there were some tumors observed. At 0.2mg/m3, there was no tumors but local inflammation. At 0.05mg/m3, there was no adverse effects of any kind).

Exposure Limits: see Section 2 under Hazardous Ingredients

Irritancy of Product: Eye and Lung irritant

Sensitization: none known

Reproductive Toxicity: none known

Mutagenicity: none known Carcinogenicity: none known Teratogenicity: none known

Synergistic Products: none known

#### SECTION 7 - PREVENTATIVE MEASURES

**Respiratory Protection:** Use NIOSH/OSHA approved dust respirator whenever dust levels exceed recommended exposure limits.

Gloves: rubber glove for dry product and rubber with non

slip coating or surface for wet product

Eye Protection: splash proof safety goggles or glasses

Footwear: rubber, chemical resistant

Issue: 10/29/04

Clothing: long sleeve

Other:

Engineering Controls: General and/or local exhaust ventilation to control dust levels below exposure limits.

**Leak and Spill Procedures:** Sweep, scoop up or vaccum spilled material. Reuse if possible or dispose in accordance with local regulations. Note that product becomes very slippery when wet.

**Waste Disposal:** Dispose of in accordance with local environmental regulations. US EPA does not define this product as hazardous waste under RCRA. Disposal into an approved sanitary landfill is acceptable.

**Handling Procedures and Equipment:** Use good hygiene practices. Avoid contact with eyes. Avoid breathing dust. Eye wash and safety shower should be available in the immediate work area.

**Storage Requirements:** Store in a cool, dry place away from incompatibles. Do not mix with any other chemicals. Keep container closed when not in use. Keep from freezing and temperatures below 30°C.

# Waste Paint Hardener (Retail & Industrial)

## **Special Shipping Information:**

#### For Retail Use

Canadian WHMIS Classification: Exempt USA OSHA (29 CFR 1910.1200): Exempt Canadian TDG Classification: Not Regulated USA DOT (49 CFR 172.101): Not Regulated

#### For Industrial(Commercial) Use

Canadian WHMIS Classification: D2A, D2B

USA OSHA (29 CFR 1910.1200): Irritant, Target Organ Effects (Chronic)

Canadian TDG Classification: Not Regulated USA DOT (49 CFR 172.101): Not Regulated

## **SECTION 8 – FIRST AID MEASURES**

**Inhalation:** Remove victim to fresh air, apply artificial respiration if necessary. Seek medical help.

**Ingestion:** If large quantities are swallowed, seek medical help.

**Skin Contact:** Wash thoroughly with water. If irritation persist, seek medical attention.

**Eye Contact:** Flush immediately with water for 15-20 minutes.

SECTION 9 - OTHER INFORMATION									
REVISIONS:	October 29, 2004	SUPERCEDES:	July 3, 2003						
PREPARED BY:	Technical Department, Customer service- 800-663-9274, Manufacturing- 604-526-0802								
DISCLAIMER:	This Material Safety Data Sheet was prepared using information provided by CCINFO. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Napier Environmental Technologies expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.								

Issue: 10/29/04